

HI - STANDARD HYDRAULIC POWER UNIT SPECIFICATIONS

Sr. No	DESCRIPTION	SPECS
1	SKID CERTIFICATE	MPI, LOAD TEST and ZONE II by third party
2	LENGTH	2500 MM
3	WIDTH	1200 MM
4	HEIGHT	1800 MM
5	TOTAL WEIGHT (WITH HYD OIL and FUEL)	2500 KGS
6	HYDRAULIC RESERVOIR CAPACITY	460 LTRS
7	HYDRAULIC OIL WEIGHT APPROX	400 KGS
8	FUEL RESERVOIR CAPACITY	110 LTRS
9	FUEL WEIGHT APPROX	88 KGS
10	DIESEL ENGINE	F6L912 NATURALLY ASPIRATED AIR COOLED ENGINE
11	HYDRAULIC FLOW / PRESSURE OUTPUT	22 LPM @ 550 Bar
12	HYDRAULIC OIL OPERATING TEMPERATURE	80 Deg C
13	HYDRAULIC SYSTEM	OPEN CENTRE / OPEN LOOP
14	HYDRAULIC HOSES and FITTINGS	GATES USA
15	OVERSPEED SHUTDOWN VALVE	CHALWYN
16	ENGINE EXHAUST SPARK ARRESTOR	NELSON USA
17	PRE-ENGAGE STARTER MOTOR	SPRING STARTER